


HPro VFD Mz SERIES

E302 | E303 | E308

Designed for industrial or business environments the HPro Misting module provides for precise solutions for installation of medium and large dimension, The patented mechanics with axial cam combined with a high efficiency pumping unit is supported by

electronic management by means of a further enhanced Soft Touch electronic board. The unit is contained in a AISI 304 stainless steel chassis equipped with a cooling fan.

EDDY 5
CONTROL PANEL

REMOTE PANELS OVER IP

WEB INTERFACE
CONTROL BY TABLET
PC AND SMARTPHONERJ45 ETHERNET
PLUG

DIG. PRESSURE READER

HIGH PRESSURE RELEASE
SOLENOID VALVE


NEW
DRAIN
BUILT-IN SYSTEM
NOT NEED
EXTERNAL
DISCHARGE

AXA SIMMM PUMP
900 RPM MOTOR < 50 dB

DIG. FLOW RATE MEETER


INSIDE COOLING FAN (2)

RO SYSTEM AND REMOTE
ON/OFF CONTROLSOCKETMODBUS RS485
DIGITAL INTERFACERADIO REMOTE CONTROL
ON/OFF PUMP AND FANFANS SOCHET
(230/115 VOLT - 10 AMPS)HUMIDITY/TEMPERATURE PROBE
MAX 4 WITH MULTI READING



TECHNICAL DATA

- SIMMM pump AXA model with no overheating system (CE approved)
- Patented flow rate valve (large range of nozzle numbers with the same model)
- Max working pressure up to 105 Bar
- Professional gauge
- Safety water pressure switch
- High pressure release solenoid valve
- "H" class motor with low speed (900 rpm)
- Thermal protection
- Lowest noise level 50 dB
- Low voltage control panel (12 volt)
- Radio remote control
- Digital cycling timer
- Digital water litre counter
- Digital pressure reader
- Temperature and humidity program
- AISI 304 stainless steel cabinet
- Built-in cooling fan
- Anti-Legionella Pneumophila automatic system equipped with certified products
- Reverse Osmosi connection socket
- Remote on/off control
- Multiply control panels over IP ethernet connections
- Datalogger of all the pump parameters
- Firmware update
- Remote on/off control
- Modbus RS485 digital interface
- Weekly timer
- Control via LAN, by any smartphone, tablet, PC or Mac
- Digital alarms on display warning message sent by SMS or by Email
- Washing line high pressure solenoid valve
- Automatic fan On/Off switch (230 volt plug built-in)
- Auto program
- Self-diagnosis
- Digital alarms with display warning message
- Soft touch panel
- High efficiency VFD



MODEL	E305	E306	E307
PRESSIONE (BAR)	70-105	70-105	70-105
NOZZLES NUMBER (0.2 MM)	10-60	20-150	60-250
PUMP	SIMMM AXA	SIMMM AXA	SIMMM AXA
MIN FLOW RATE (LT/MIN)	1.2	1.90	5.70
MAX FLOW RATE (LT/MIN)	4.68	9.8	20
MOTOR SPEED (RPM)	1.450	1.450	1.450
VOLTAGE (VOLT)	230/115 50/60 Hz.*	230/115 50/60 Hz.*	230/115 50/60 Hz.*
POWER (KW/H)	0.92	0.92	2.90
MAX DAILY USE (HOURS)	24	24	24
WEIGHT (KG)	36	36	36
DIMENSIONS LXHPX (CM)	65x44x42	65x44x42	65x44x42

* ON REQUEST